



BBT ANTENNAS INC

Model NO: BBT-0660CL0306H2

Type : 2T2R Ceiling Antenna

Application:

- ★Support 5G、6G communication system
- ★For indoor wireless coverage system (For indoor DAS)



Features:

- ★Broadband ,Low PIM,Low VSWR, stable performance
- ★Size thin, Attractive appearance
- ★Regular ceiling installation, easy to install and use.

Specifications:

Electrical				
Model Number	BBT-0660CL0306H2			
Frequency Range	617-960MHz	1710-2700MHz	3300-4200MHz	4900-6000MHz
Polarization Type	Horizontal×2			
Gain	3dBi	4.5dBi	5.5dBi	6dBi
3dB Beam-Width. H-Plan	360°			
3dB Beam-Width. E-Plan	60°	50°	35°	30°
VSWR	≤1.8	≤1.8	≤1.8	≤1.8
Port to Port Isolation	≥16dB	≥20dB	≥23dB	≥23dB
Intermodulation IM3(2*43dBmcarrier)	≤-150dBc			
Input Impedance	50Ω			
Max Input Power.	50W			
Mechanical				
Connector Type	2×4.3-10-Female			
Cable	SFF-50-3			
Cable length	25cm			
Dimensions H*W*D (mm)	Φ280*18(mm)			
Radome Material	ABS			

Radome color	White
Operating Temperature Rang	-40°C/+60°C

BBT ANTENNAS INC

Tel: (+86) 0757-66898899

<http://www.bbtantennas.com>