



BBT ANTENNAS INC

Model NO.: BBT-0642CL0204V-206

Type : Ceiling Antenna

Application:

★For indoor distributed wireless coverage system

(For indoor DAS)

★Support LTE、3G、4G、5G、GSM、CDMA Wireless system



Features:

★Wide bandwidth,Low VSWR, stable performance,Omnidirectional

★Small size, attractive appearance



★Regular ceiling installation, use conveniently

Specifications:



Electrical			
Model Number	BBT-0642CL0204V-206		
Frequency Range	698-960MHz	1710-2700MHz	3300-4200MHz
Polarization Type	Linear H/V		
Gain	2.15dBi	4dBi	4dBi
3dB Beam-Width. H-Plan	360°	360°	360°
3dB Beam-Width. E-Plan	80°	60°	60°
VSWR	≤2.0	≤1.8	≤1.8
Intermodulation IM3(2*43dBmcarrier)	≤-150dBc		
Input Impedance	50Ω		
Max Input Power.	50W		
Lightning Protection	DC Grounded		
Mechanical			
Connector Type	2×4.3-10 Female		
Cable	SFF-50-3		
Cable length	25cm		
Dimensions H*W*D (mm)	Φ207*55(mm)		
Radome Material	ABS		
Radome color	White		

Radiation Pattern:

698-960MHZ



1710-2700MHZ、3300-4000MHZ



BBT ANTENNAS INC

Tel: (+86) 0757-66898899

<http://www.bbtantennas.com>

Product specification datasheet for reference only, the real product is based on the physical.