

Commercial & Industrial ESS

Features & Advantages

- Compact Size**

- Cabinet covers no more than 1.7 m²
- Energy density improved by 40%

- Modular Design & Scalable**

- Support cabinet-level parallel connection and cluster control
- Support flexible capacity expansion
- Easy installation & connection

- Safe & Cost-effective**

- AI diagnosis system enables pre-alarm and faults location
- Integrated battery modules with fire protection and isolation
- System efficiency higher than 91%

- Minimal Maintenance**

- Multi-scenario intelligent battery management system
- Cloud EMS, Millisecond-level precise control
- Fast state monitoring and unattended design



Technical Specifications

Model	PowerHub-372/H
Battery PACK	
Cell type	LFP280Ah
Nominal capacity	372.7kWh
Thermal management	Liquid cooling
AC side	
AC rated power	186kW
Max. AC power	220kW
AC rated voltage	690Vac
Way of connection	Three-phase & three-wire
Voltage range	586~759V
Adjustable range of power factor	-1~1
Rated grid frequency	50/60Hz
Range of rated grid frequency	45~55Hz/55~65Hz
Max. THDI	<3% (at rated power)
DC component	<0.5%
Thermal management	Forced air cooling
Communication	
Communication interface	RS485/Ethernet
Communication protocol	MODBUS-RTU/MODBUS-TCP/IEC61850
Battery energy system	
System efficiency	≥91%
Charge/discharge ratio	0.5C
DOD	95%
Number of cycles	6600
Ingress protection level	IP54
Environment temperature	-30~50°C
Environment humidity	0~95%RH no condensing
Max. altitude	2000m
Dimension (width*depth*height)	1300*1300*2450mm
Weight	3600kg
Fire control system	Combustible gas, smoke and temperature detectors + module-level fire extinguishing system (Perfluorohexanone) + water firefighting system (reserved)